

GENERAL NOTES:

- A. PARTITION DIMENSIONS ARE GIVEN TO THE FACE OF STUD UNLESS OTHERWISE NOTED.
- B. DOOR AND WINDOW OPENING LOCATIONS ARE DIMENSIONED TO ROUGH OPENING OR CENTERLINE OF OPENING. COORDINATE WITH DOOR
- SCHEDULE AND WINDOW TYPES, SHEET A6.2.
- C. VERIFY ALL EXISTING CONDITIONS IN THE FIELD.
- D. ALL GYPSUM WALL BOARD TO BE FIRE RESISTIVE TYPE 'X'. PROVIDE MOISTURE RESISTANT GYPSUM BOARD ON WALL WALLS WITHIN TOILET ROOMS AND JANITOR CLOSETS, BEHIND CERAMIC WALL TILE, AND BEHIND OTHER FINISHES THAT GENERATE MOISTURE, U.O.N.
- E. GYPSUM WALL BOARD SHALL EXTEND FULL HEIGHT OF WALL TO UNDERSIDE OF STRUCTURE ABOVE UNLESS OTHERWISE NOTED. SEE WALL TYPES.
- F. RE: A6.2 FOR DOOR, WINDOW AND FRAME SCHEDULES.
- G. RE: A6.1 FOR FINISH SCHEDULE.
- H. RE: A9.1 AND 9.2 FOR CEILING INFORMATION.
- J. RE: A10.1 & A10.2 FOR FURNITURE AND EQUIPMENT PLAN.
- K. EXTERIOR FINISH INFORMATION IS NOT INDICATED NOR DIMENSIONED ON FLOOR PLAN. REFER TO EXTERIOR ELEVATIONS, SECTIONS, AND DETAILS FOR ADDITIONAL INFORMATION.
- L. THE HINGE SIDE OF ALL DOOR FRAMES SHALL BE MOUNTED 4"[0.102m] FROM ADJACENT PERPENDICULAR WALL U.N.O.
- M. THE DRAWINGS INDICATE LOCATION, DIMENSIONS, REFERENCE, AND TYPICAL DETAILS OF CONSTRUCTION. THE DRAWINGS DO NOT INDICATE EVERY CONDITION - WORK NOT PARTICULARLY DETAILED SHALL BE OF CONSTRUCTION TO PARTS THAT ARE DETAILED. THESE DRAWINGS HAVE BEEN DEVELOPED FROM RECORDS FURNISHED BY THE OWNER AND FIELD SURVEYS. MATERIALS, DIMENSIONS, WALL THICKNESS', ROUGH OPENINGS, PATTERNS, AND THE LIKE ARE INTERPRETATIONS OF THOSE RECORDS AND SHALL BE FIELD VERIFIED BY THE CONTRACTOR. ANY DISCREPANCIES SHALL BE BROUGHT TO THE ATTENTION OF THE ARCHITECT PRIOR TO COMMENCING WITH THE WORK.
- N. PROTECT ALL EXISTING WORK TO REMAIN FROM DAMAGE DURING CONSTRUCTION. ANY MATERIALS, SYSTEMS, COMPONENTS, FINISHES, AND THE LIKE, DAMAGED DURING CONSTRUCTION SHALL BE REPAIRED OR REPLACED TO OWNER'S ACCEPTANCE AT CONTRACTOR'S EXPENSE.
- P. PAINT THE HEATING WATER PIPING THAT IS EXPOSED TO VIEW BELOW THE UNIT. PAINT ALL WALL SURFACES THAT ARE VISIBLE BEHIND HEATING UNIT WHEN COVER IS IN PLACE.
- Q. THE CONTRACTOR SHALL FIELD VERIFY EXISTING PAINT MATERIALS AND FINISHES. APPLY THE APPROPRIATE SEPARATION COAT (PRIMER/BONDING COAT) BETWEEN ALL NON-COMPATIBLE COATINGS (I.E. WHERE NEW WATER-BORNE ACRYLIC IS TO BE INSTALLED OVER EXISTING OIL BASE PAINT).
- R. ASSURE THAT ALL REQUIRED BACKING IS INSTALLED IN WALLS PRIOR TO INSTALLING DRYWALL. THIS INCLUDES BACKING FOR WALL-MOUNTED DOORSTOPS.

LEGEND:

FIRE EXTINGUISHER CABINET, RE; A7.2-14 AND 15.

CORNER GUARD

PROJECT NO.

DRAWING NO.

531-10-114

----- NEW CONSTRUCTION

----- EXISTING CONSTRUCTION

DEPARTMENT OF VETERANS AFFAIRS

95% SUBMISSION JOHN D. MAULIN, ARCHITECT C.W. MOORE PLAZA 250 S. 5TH ST BOISE, IDAHO PHONE: 208-343-4635 FAX: 208-343-1858 THESE DRAWINGS AND SPECIFICATIONS, AS INSTRUMENTS OF SERVICE, ARE AND SHALL REMAIN THE PROPERTY OF THE ARCHITECT / ENGINEER WHETHER THE PROJECT FOR WHICH THEY ARE MADE IS EXECUTED OR NOT. THESE C.W. MOORE PLAZA 250 S. 5TH ST. • BOISE, ID 83702 ANY PERSON OR ENTITY ON OTHER PROJECTS, FOR ADDITIONS TO THIS PROJECT, OR COMPLETION OF THIS (208) 343-4635 • FAX (208) 343-1858 PROJECT-WHEN PHASED-WITHOUT THE WRITTEN CONSEN OF CSHQA OR ITS AFFILIATES. Copyright@2011 http://www.cshqa.com

REVISIONS

PRELIMINARY NOT FOR CONSTRUCTION DIMENSIONED FLOOR PLANS APPROVED: DIVISION CHIEF

RENOVATE BUILDING 33 CHECKED DRAWN BUILDING NUMBER JMO BKS APPROVED: SERVICE DIRECTOR LOCATION BOISE, IDAHO

PROJECT TITLE

VAMC